

EnduroTM Tanks



**Stand Model
(Vertical)**



**In-Line Model
(Pipe Mounted)
(Buried)**



**Horizontal Model with
Pump Mounting Bracket**

Deep drawn steel shells provide maximum material strength.

Inner shell prevents diaphragm from over-expanding.

Heavy duty diaphragm made of finest quality butyl rubber. Separates air and water, maintains air charge.

Tank features a durable polypropylene interior liner. Meets FDA requirements.

Maximum working pressure: 125 PSI.

Temperature rating: Maximum 120° F.

Stainless steel system connection on all stand, in-line, and buried models.

Two coat, high durability exterior finish.

Heavy duty base eliminates corrosion due to condensation and exposure to the elements. Made of high density polypropylene.

Horizontal models feature a universal jet pump mounting bracket and two (2) bolt-on, corrosion-resistant, high density polypropylene feet for installations with limited headspace, such as under mobile homes.



Red Jacket Water Products is a licensed trademark.

Enduro is a registered trademark.

The ITT Engineered Blocks symbol is a registered trademark and tradename of ITT Industries.

Visit us at: www.redjacketwaterproducts.com

Effective March, 2004

BRJTANK



ITT Industries

EnduroTM Tanks

	Model No.	Total Volume (Gals.)	Drawdown in Gals. at System Operating Pressure Range of			Max. Drawdown Vol. (Gals.)	Pre-Charge PSI	System Connection	Dimensions		Shipping Weight	Height From Floor to Center of Base Opening
			20/40 PSIG	30/50 PSIG	40/60 PSIG				Diameter	Height		
Stand Models	ET45	13.9	5.1	4.3	3.7	8.4	38	1" NPTF	15 ³ / ₈	24 ¹⁵ / ₁₆	23	3 ³ / ₈
	ET60	19.9	7.3	6.1	5.3	12.1	38	1" NPTF	15 ³ / ₈	32 ³ / ₈	34	
	ET80	25.9	8.9	7.7	6.7	13.9	38	1" NPTF	15 ³ / ₈	39 ⁹ / ₁₆	43	
	ET80EX	25.9	8.9	7.7	6.7	13.9	38	1" NPTF	15 ³ / ₈	42 ³ / ₈	43	7 ¹ / ₄
	ET100	31.8	11.8	9.9	8.6	13.8	38	1" NPTF	15 ³ / ₈	47 ¹ / ₄	52	3 ³ / ₈
	ET100S	31.8	11.8	9.9	8.6	13.8	38	1" NPTF	22	28	56	3 ³ / ₈
	ET140	45.2	16.5	13.9	12.1	27.3	38	1 ¹ / ₄ " NPTF	22	36 ³ / ₁₆	64	
	ET200	65.1	23.9	20.0	17.4	39.3	38	1 ¹ / ₄ " NPTF	22	48 ³ / ₈	89	
	ET250	83.5	30.9	25.9	22.5	50.8	38	1 ¹ / ₄ " NPTF	26	46	116	
	ET260	84.9	31.2	26.2	22.8	44.7	38	1 ¹ / ₄ " NPTF	22	60 ¹ / ₁₆	113	3 ³ / ₈
ET350	115.9	42.9	35.9	31.3	70.5	38	1 ¹ / ₄ " NPTF	26	61 ³ / ₁₆	161	3 ¹ / ₂	
Buried Models	ET45B	13.9	5.1	4.3	3.7	8.4	38	1" NPTM	15 ³ / ₈	21 ¹ / ₁₆	23	NOTES: * Compatible with only certain Red Jacket Pumps. P = Pipe mounted EX = With base extension B = Buried H = Horizontal with bracket (All dimensions are in inches and weight in lbs. Do not use for construction purposes.)
	ET60B	19.9	7.3	6.1	5.3	12.1	38	1" NPTM	15 ³ / ₈	28 ¹ / ₂	33	
	ET140B	45.2	16.5	13.9	12.1	27.3	38	1 ¹ / ₄ " NPTM	22	32 ³ / ₁₆	63	
	ET200B	65.1	23.9	20.0	17.4	39.3	38	1 ¹ / ₄ " NPTM	22	44 ¹ / ₄	87	
In-Line Models	ET6P	2.0	0.7	0.6	0.5	1.2	38	3/4" NPTM	8	11 ¹⁵ / ₁₆	8	
	ET15P	4.5	1.7	1.4	1.2	2.7	38	3/4" NPTM	11	13 ¹⁵ / ₁₆	12	
	ET25P	8.2	3.1	2.6	2.2	4.5	38	3/4" NPTM	11	23 ¹ / ₁₆	21	
	ET45P	13.9	5.1	4.3	3.7	8.4	38	1" NPTM	15 ³ / ₈	21 ¹ / ₁₆	24	
Horizontal Models w/ Bracket	ET25H	8.2	3.1	2.6	2.2	4.5	38	3/4" NPTM	11	24 ³ / ₁₆	23	
	ET45H	13.9	5.1	4.3	3.7	8.4	38	1" NPTM	15 ³ / ₈	22 ³ / ₁₆	26	
	ET60H	19.9	7.3	6.1	5.3	12.1	38	1" NPTF	15 ³ / ₈	33 ³ / ₈	36	

ACCESSORIES



■ **AW39 Bracket:**
 Universal pump mounting bracket for use on all stand model tanks.

Order No.	Description	Wt. (bs.)
AW39	Universal Jet Pump Bracket	2

